

## **PROCESS FOR CONTINUOUSLY IDENTIFYING DRAWN METAL PARTS**

### **Cross Reference to Related Applications**

**[0001]** This application claims priority of provisional application Serial No. 60/437,531 filed December 31, 2002.

### **Background of the Invention**

**[0002]** This invention relates to a high volume manufacturing process for continuously producing, inspecting and packing drawn metal parts that require a series of sequential intermediate operations to produce finished drawn metal parts. An example of high volume manufacturing of drawn metal parts is the production of battery cans, which are used as the primary battery casing for commercial cells, such as A, AA, AAA, C, D, F, M, etc.

**[0003]** Manufacturing of battery cans according to the prior art is generally accomplished by a batch and queue process in the following manner. A redraw press accepts narrow strip stock from a payoff reel and performs blanking, cupping and subsequent redraw operations. The entire battery can is manufactured in each stand-alone redraw press and the cans are collected in bulk in containers. The press operator and/or toolmaker manually inspect the dimensional and cosmetic attributes of the can. A pre-determined number of cans are removed randomly and inspected. Next the containers of parts from the press are moved to a staging area near a washer/dryer machine. The washer/dryer, which removes the drawing lubricant, is typically a rotary bulk washer with a cob dryer. An operator feeds the cans into the inlet of the washer. The washed cans are caught in bulk hoppers or cartons.

**[0004]** Next the washed cans are moved to a staging area near a coating machine. The coating machines apply thin film of coating material to the interior of the can. The cans are dried in bulk in a curing oven. An operator feeds the cans to the coaters. The cans are inspected for proper coating and then placed into the final packaging containers.

**[0005]** The batch and queue process described above has several disadvantages. The narrow strip stock produces significant scrap, due to unusable material at the edge of the strip. The required coil changes to feed the narrow strip stock to the redraw press lead to inefficiencies in operation. Damage can occur due to parts contacting other parts in the batch containers. Rejection of parts due to dimensional, coating and cosmetic defects may be

inconsistent due to using different inspectors.

[0006] Another disadvantage is the requirement to follow the parts produced by a particular tool through the manufacturing process by keeping track of the batch container corresponding to each tool. This is necessary in order to halt operation from a particular redraw press and take corrective action if dimensional changes occur due to tool wear. Manual operator time is required to move batch containers from one operation to the next while retaining identification of the batch with the tool producing the part.

[0007] Accordingly, one object of the present invention is to provide a continuous high volume process for manufacturing and packing drawn metal parts.

[0008] Another object of the invention is to provide an improved continuous process for tracking drawn metal parts through a series of manufacturing operations so as to identify the tool which was the source of the parts.

[0009] Still another object of the invention is to provide an improved process for continuously manufacturing and randomly inspecting parts sampled from the process, and taking corrective action.

[0010] Another object of the invention is to provide an improved process for coating and inspecting the coating on drawn metal parts.

[0011] Another object of the invention is to control the speed of intermediate manufacturing steps so as to optimize the overall flow of parts.

[0012] Another object of the invention is to maintain identification of the source of one parts through the manufacturing process all the way to final packing of finished parts.

### **Summary of the Invention**

[0013] Briefly stated, the invention concerns a process for continuously producing, inspecting and packing finished drawn metal parts in containers identified by the tool from which they were produced, comprising the steps of: providing a plurality of identified drawing press tools; supplying each one of the identified drawing press tools with a supply of metal blanks; drawing the metal blanks in the identified drawing press tools to provide segregated streams of drawn metal parts, each stream being associated with one of the identified drawing press tools; merging the segregated streams into a single ordered stream of drawn metal parts having a repeating sequential order enabling identification of the drawing press tool in which the drawn metal part was drawn; removing a drawn metal part from the

ordered stream; inspecting the removed part; providing a plurality of containers corresponding to the plurality of identified drawing press tools; and packing the finished drawn metal parts from the ordered stream into the containers respectively corresponding to the identified drawing press tools.

[0014] In its preferred form, the invention includes the steps of: providing a source of initially drawn metal cups; providing a plurality of identified drawing press tools; supplying each one of the plurality of identified drawing press tools with a supply of metal cups from said source; drawing the metal cups in the plurality of identified drawing press tools to provide a plurality of segregated streams of drawn metal parts, each stream being associated with one of the identified drawing press tools; merging said segregated streams into a single ordered stream of drawn metal parts having a repeating sequential order enabling identification of the drawing press tool in which the drawn metal part was drawn by the location of the metal part in the ordered stream; providing a conveyor having a segregated pocket for each of the drawn metal parts; inserting the drawn metal parts into the segregated conveyor pockets in the sequential order; removing a drawn metal part from one of said conveyor pockets in the ordered stream; inspecting the removed part and taking any required corrective action on the drawing press tool identified by the pocket on said conveyor from which the drawn metal part was removed; performing additional manufacturing steps on the ordered stream to provide finished drawn metal parts, while maintaining empty pockets on the conveyor corresponding to the locations where drawn metal parts are removed; providing a plurality of containers corresponding to the plurality of identified drawing press tools; and packing the finished drawn metal parts from the ordered stream into the containers respectively corresponding to the identified drawing press tools.

### **Drawing**

[0015] The invention will be better understood by reference to the following description, taken in connection with the accompanying drawing, in which:

[0016] Fig. 1 is a simplified block diagram of the manufacturing process,

[0017] Fig. 2 is a schematic representation of a merge and sequence machine,

[0018] Fig. 3 is a schematic representation of portions of a conveyor, with means to remove a part for inspection,

[0019] Fig. 4 is a schematic representation of apparatus used to coat drawn metal parts,

[0020] Fig. 5 is a schematic diagram of the packing process, and

[0021] Fig. 6 is a perspective view showing the actual placement of equipment, with simplified diagram of the process computer controls.

### General Description of the Process

[0022] Referring to Fig. 1 of the drawing, a coil payoff system 10 feeds a cupping press 12 with a wide strip of thin metal from a coil. Cupping press 12 performs a blanking and drawing operation to produce seven cups at a stroke, which are fed onto a magnetic conveyor 14. The flow of parts from the cupping press 12 divide into two "cells" A and B. Either cell A or B may operate independently of the other throughout much of the manufacturing process, even though they rejoin to share some equipment toward the end of the process.

[0023] Conveyor 14 supplies the cups to redraw presses 16, 18 in cell A and to redraw presses 20, 22 in cell B. In order to provide for possible downtime of cupping press 12 and/or redraw presses, part accumulators 24, 26 act as buffers to receive or discharge cups as necessary. Accumulators 24, 26 are towers with helical tracks for temporary storage of parts with control means to switch parts to the presses if the cupping press is not operating, but any type of storage capable of accumulating and discharging parts via conveyors will be suitable.

[0024] The redraw presses 16, 18, 20, 22 each are equipped with at least two sets of redraw stations, hereinafter defined "tools". As defined in this patent application, a "tool" (singular) is actually a set comprising several redraw punches and dies, which successively draw the cups into the final dimensional shape of a battery can and cut off the top rim of the can. Thus, in the illustration shown, each press handles two "tools" and, therefore, produces two parts during each stroke. However, more than two tools per press are also possible.

[0025] Battery cans from each of the tools in each of the redraw presses are discharged onto a separate conveyor, such as that indicated by reference number 28. Means are provided to remove a sample for local inspection as shown at 30. While a single conveyor 28 and its inspection station 30 are indicated on the drawing for tool number four of redraw press 18, a similar arrangement is placed at the tool discharge of each redraw press. If there are more than two tools in each redraw press, additional conveyors will be required, one for each tool.

[0026] Battery cans 1, 2, 3, 4 from presses 16, 18 in cell A are separately accumulated in four serpentine tracks, one for each tool, in an accumulator 32. Similarly battery cans 5, 6, 7, 8 from redraw presses 20, 22 in cell B are separately accumulated in four serpentine tracks in

accumulator **34**.

[0027] A special ordered merge device **36** in cell **A** and an identical device **38** in cell **B** perform an ordered merge operation to be described later in detail. Briefly the separate streams of parts from the tools of each of the presses are merged into a single ordered stream of parts maintaining a sequential order that enables identification of the tool by the location of the part in the stream. This ordered stream of parts is represented by the dashed lines **40 - 42** representing the conveyors from the ordered merge **36, 38**.

[0028] An automatic dimensional inspection machine **44** is shared by both cells **A** and **B** and equipped with instruments, which measure certain critical dimensions in the battery cans. Part ejectors **46, 48** are precisely controlled to remove a part from a pocket on a conveyor **40, 42** and place it in the dimensional inspection equipment **44**. It is important to note that the empty pocket in the conveyor from which the part is removed is maintained throughout the manufacturing process, so that the integrity of the ordered stream is maintained as the battery cans move through the process. This integrity is maintained when parts are transferred from one conveyor to the next.

[0029] Battery cans from cell **A** and cell **B** are conveyed to washer/dryers **50, 52** respectively. There, the drawing compound is removed and the battery cans dried. Thereafter, each washer/dryer **50, 52** supplies a buffer **54, 56** respectively. Buffers **54, 56** are maintained half-full by a moveable bridge mechanism. The buffer level controls the speed of the coating/inspection conveyor downstream of it.

[0030] Optical camera inspection systems **58, 60** measure the streams of battery cans from the buffers **54, 56**. The parts are fed in order maintaining gaps for any missing parts, onto special motion converting conveyors **62, 64** equipped with coating guns. These devices will be described further in detail, but, briefly stated, the continuously moving stream of parts is converted to an intermittently moving or indexed motion having a dwell time and a move time. During the dwell time, the cylindrical battery cans are rotated while they are sprayed on the inside with coating guns. Following the coating operation, an automatic optical inspection system at **66, 68** inspects internal coating, and any cosmetic anomalies on the exterior of the battery can. Rejects are automatically removed by part ejectors **70, 72**. The parts, still segregated in the respective conveyor pockets for the two cells **A, B** move to a coating dryer **74** and, from there, to the pack operation indicated at **76**.

### Ordered Merge Operation

**[0031]** While the preceding section describes the overall process for manufacturing drawn metal parts in a general discussion, several aspects of the process will be described in detail. One of these is the ordered merge operation, which combines the separate streams of parts from the separate drawing press tools in such a way that the sequence is always the same and is repeated periodically. In this way, the segregated stream of parts are merged into a single ordered stream of drawn metal parts having a sequential order which enables identification of the drawing press tool in which the part was made.

**[0032]** **Fig. 2** illustrates in simplified diagrammatic fashion the ordered merge operation. It will be understood that the actual configuration will vary according to size and type of the parts, as well as variations in the components. The ordered merge machine is shown generally at **80** and comprises four separate accumulating receptacles **82, 84, 86, 88**. These are part of the accumulators **32** or **34** shown in **Fig. 1**. Each such accumulating receptacle receives drawn metal parts from a different tool, in this case parts **1, 2, 3** and **4** coming from tool one, tool two, tool three, and tool four respectively of presses **16, 18** (**Fig. 1**). Whenever parts **1, 2, 3** and **4** are depicted in the following drawings, they are deemed to be from their corresponding source tool, although they may appear at different places in the processes to be described. Accumulating receptacles **82, 84, 86, 88** supply feed wheels **90, 92, 94, 96** respectively. The feed wheels supply parts to a merge wheel **98**, which feeds a conveyor **100**. The feed wheels have pockets, such as **102**, and the merge wheel **98** has pockets, such as **104**. The feed wheels are mechanically geared to the merge wheel, so that a pocket **102** on an feed wheel registers with every fourth pocket **104** on the merge wheel as the wheels turn.

**[0033]** If there are more than two tools on each redraw press, e.g., three tools, the feed wheels and index wheels must be modified accordingly to include the proper number of pockets.

**[0034]** Conveyor **100** is designed to have a carrier belt **106**, with dividing walls **108** providing segregated pockets **110**. The speed of the conveyor **100** is timed to coincide with the speed of the merge wheel **98**, so that the pockets **104** on the merge wheel feed the segregated pockets **110** on the conveyor in precise order. **Fig. 2** illustrates that accumulating receptacle **86** was temporarily empty, so that feed wheel **94** was previously not feeding parts **3** to the designated pocket on merge wheel **98**. Therefore the segregated pockets **110** on conveyor **100** are temporarily empty, but the single ordered stream of parts continues to flow

to the next intermediate processing operation.

### **Part Ejectors**

**[0035]** The process provides for removal of parts at various points of the process for dimensional inspection, for local tool-maker inspection, for defects located at any point in the process. Such part ejectors are shown on **Fig. 1**, for example, at **29, 46, 48, 70, 72**. **Fig. 3** illustrates schematically, in simplified form, the operation of such a part ejector. A conveyor **112** is made up of articulated links **114** hinged together at pivot points (not shown). Each such link has a divider wall **116** projecting upwardly from the link platform. The space between divider walls **116** provides segregated pockets for the parts **1, 2, 3, 4** supported on the platforms of the articulated links **114**. The drawn metal parts are cylindrical and each has an open end **118**, as is typical of battery cans and similar drawn parts.

**[0036]** Removal of parts is accomplished with an air jet **120** having a tip **122** aligned with the open end of the parts, and a collection tube **124** having an open end **126** aligned with the axis of the air jet. The collection tube is provided with directed openings **128** which are, in turn, surrounded by a manifold **130**. When it is desired to remove a part, air jet **120** and manifold **130** are supplied with a blast of high-pressure air, pushing the part **3** into the open end **126** of the collection tube **124**. Air entering the manifold **130** and openings **128** propels the part **3** through the tube to a collection point (not shown).

**[0037]** This arrangement is known as a “bazooka”, and may be either automatically or manually actuated to remove a part from a segregated pocket. Since the parts are in sequence, the part corresponding to any selected tool source may be removed. The location of the pocket on the conveyor is a function of the conveyor speed that is precisely known by an encoder, and controlled by a programmed logic computer (see **Fig. 6**).

### **Coating Operation**

**[0038]** Referring to **Fig. 4** of the drawing, a conveyor **132** is provided with a known type of mechanism (not shown) to convert a continuous movement to an indexed movement having a move time and a dwell time. The coating operation involves spraying a conductive coating into the open ends of the drawn metal parts. Coating is accomplished by means of coating spray guns **A, B, C, D**. These are spaced along conveyor **132**, which is moving from left to right in the drawing, so that each spray gun is automatically actuated to spray a jet of

coating material into the open end of the part during the dwell time of conveyor **132**.

Rotating apparatus (not shown) is also provided to rotate the cylindrical parts about their axis while the spray gun is active so as to obtain a uniform coat. Spray guns **A, B, C, D** are spaced along conveyor **132**, so that coating gun **A** coats part **1**, coating gun **B** coats part **3**, coating gun **C** coats part **4**, and coating gun **D** coats part **2**.

**[0039]** Because of the possibility that one or more coating guns may become inoperative, a unique system is employed to enable a coating gun to take over the job of an inoperative coating gun, while continuing to process its previously assigned part. The coating guns are capable of firing twice as fast as their normal firing rate. Also, coating guns **B** and **C** are able to shift one position along conveyor **132** to the alternate respective positions indicated by reference letters **B', C'**.

**[0040]** Method 1: If gun **B** should become inoperative, it will be observed that coating gun **A** may be operated at twice its regular firing rate to coat parts **1** and **3**. Similarly, gun **B** may take over for gun **A** should gun **A** become inoperative. In a similar manner, guns **C** and **D** may assume the duties for each other by firing at twice the normal rate.

**[0041]** Method 2: Should both guns **C** and **D** become temporarily inoperative, gun **B** may be shifted to position **B'**. With both guns **A** and **B'** firing at twice the normal rate, they can take over the job of coating all four parts. In a similar manner if both guns **A** and **B** become temporarily inoperative, gun **C** may be shifted to **C'** and guns **C'** and **D**, firing at twice the normal rate will coat all four parts.

**[0042]** The coated parts are inspected by an optical inspection system **134** and removed by a parts ejector **136** if they should be unacceptable.

### **Packing Segregated by Tool**

**[0043]** Referring to **Fig. 5** of the drawing, a packing area shown generally as **138** receives an ordered stream of parts **1, 2, 3, 4** on a conveyor **140** from cell **A** and a second ordered stream of parts **5, 6, 7, 8** on a conveyor **142** from cell **B**. In keeping with the philosophy of the inventive process, some of the pockets of the conveyors may be empty because of removal of parts upstream for various purposes. A series of receptacles **144** are provided, each one from a different tool. A U-shaped conveyor **146** carries boxes of parts from a box filling area shown generally as **148** to a box collection area shown generally



as 150.

**[0044]** Empty boxes are supplied along a first table (or conveyor) 152. Boxes being filled are stationed along a second table (or conveyor) 154 and, when full, are pushed onto conveyor 146. The filled boxes are then conveyed to a specific collection station, such as the one designated at 156. From there they are removed for shipment, the boxes being coded to designate the source tool from which they were manufactured.

### **Dimensional Test Unit**

**[0045]** Referring to **Fig. 1** of the drawing, automatic dimensional inspection is carried out by dimensional test unit 44. This unit is designed to measure, via touch probes, pre-defined dimensions on the parts. The unit will measure parts from eight tools plus allowance for manual insertion/inspection of parts. The unit provides for automatic measuring, indexing and discharge of parts. A detailed description of the device as used to measure the parts is beyond the scope of this application. However, such devices are known in the prior art. Part ejectors such as previously mentioned in connection with **Fig. 3** are attached to conveyors feeding the washer/dryers 50, 52, as indicated at 46, 48 in **Fig. 1**. The parts are introduced vertically, closed end down. An electromagnetic brake holds the part momentarily, and then releases the part into the pocket in the dimensional test unit 44. When the dimensional test unit is in automatic mode, parts are requested for dimensional measurement in a pre-selected sequence. A signal is received from an encoder on the conveyor informing it that the requested part is positioned in front of the part ejector. The part ejector is activated and the part enters the dimensional test unit.

**[0046]** The dimensional test unit measures a part approximately every 10 seconds. If eight tools are running, there will be an 80-second delay between the time a part is measured and the time a part from the same tool is measured again. If a defective part is detected, a second part from the same tool should be requested as soon as possible to verify the original result. Since the line is continuing to move, there could be a considerable number of defective parts downstream, as well as those upstream from the defective tool. The dimensional test unit sends the appropriate signals to stop the press with the defective tool, to stop the discharge conveyor from the appropriate buffer 54, 56, and to activate appropriate parts ejectors to purge the line of all parts from that tool, both upstream and downstream. Corrective action on the defective tool may then be taken, while the line continues to run,

maintaining empty pockets corresponding to those pre-selected for that particular tool.

### **Process Speed Control**

**[0047]** The manufacturing system includes various safeguards and control devices to maintain production of drawn metal parts in an optimum manner, and maximize overall production, while assuring that failure or defective operation of any piece of equipment does not shut down the entire line. Reference to **Fig. 6** shows a perspective view of the actual configuration of the production line. Only cell **A** is indicated on the drawing, along with apparatus that is shared by cells **A** and **B**. The reference numbers of the pieces of equipment correspond to those in **Fig. 1**. A programmed logic computer **158** is representative of one or more programmed logic computers receiving signals and sending commands represented by phantom lines. Any deficiency in cups from the cupping press that is detected at **160** is communicated over lines **162** to controls for the spiral tower buffer **24** to augment the supply. Shortage of parts in the buffer **24** signals cupping press **12** over line **164**.

**[0048]** Press strokes per minute of the four redraw presses are detected and communicated to PLC **158** over lines **166**, **168**. Press stroke speeds are used in a computer program to set the speed of washer/dryer **50** over control line **170**. The speed of the discharge from buffer **54** and the washer/dryer discharge is set to vary in accordance with the capacity level of the buffer, speeding up as the buffer level of parts lowers and slowing down as it fills up. This is indicated by control line **172**. The merge wheel for ordered merge unit **36** is directly driven by the washer **50**. Any back up of parts into the separately fed accumulators **32** is detected at **174** and shuts down the appropriate press. The coating lines and their associated conveyors **62** are controlled by the speed of the discharge conveyor from buffer **54**, as indicated by control line **176**.

**[0049]** Therefore, it can be seen that by provision of appropriate accumulators and buffers at various stages in the process, as well as controlling the conveyor speed of intermediate upstream or downstream processing units, the continuous in-line process can continue to operate at optimum speed. This is despite the removal of parts at various points in the process for inspection or due to faulty manufacture.

**[0050]** Other modifications of the invention will become apparent to those skilled in the art and it is desired to cover all such modifications as fall within the true spirit and scope of the invention.